

**Oasis Pro Toilet****Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : Oasis Pro Toilet
Product code : 116792E
Use of the Substance/Mixture : Toilet Bowl Cleaner
Substance type: : Mixture

For professional users only.

Product dilution information : 1.0 % - 8.0 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Sanitary cleaner. Manual process
Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : Food & Beverage, Institutional, Agriculture, Textile Hygiene:
Northwich: +44 (0)1606 74488
Healthcare Leeds: +44 (0)113 232 2480
Healthcare Swansea: +44 (0)1235 239670
Poison Information Centre telephone number : Not Available

Date of Compilation/Revision : 06.06.2017
Version : 1.2

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)****Product AS SOLD**

Corrosive to metals, Category 1 H290
Skin corrosion, Category 1A H314

Oasis Pro Toilet

Serious eye damage, Category 1

H318

Product AT USE DILUTION

Not a hazardous substance or mixture., The classification of this product is based on toxicological assessment.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms

:



Signal Word

: Danger

Hazard Statements

: H290
H314

May be corrosive to metals.
Causes severe skin burns and eye damage.

Precautionary Statements

: **Prevention:**
P280

Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Phosphoric acid

Fatty alcohol ethoxylates > 5EO

Product AT USE DILUTION

Not a hazardous substance or mixture.

2.3 Other hazards

Product AS SOLD

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Product AS SOLD

Hazardous components

Chemical Name	CAS-No. EC-No.	ClassificationREGULATION (EC) No 1272/2008	Concentration: [%]
---------------	-------------------	---	-----------------------

Oasis Pro Toilet

	REACH No.		
Phosphoric acid	7664-38-2 231-633-2 01-2119485924-24	Skin corrosion Category 1B; H314 Corrosive to metals Category 1; H290	$\geq 50 - \leq 100$
Alkylamineoxides	61791-46-6 263-179-6	Acute toxicity Category 4; H302 Acute aquatic toxicity Category 1; H400 Serious eye damage/eye irritation Category 2; H319 Skin corrosion/irritation Category 2; H315	$\geq 5 - < 10$
Diethylene Glycol	111-46-6 203-872-2 01-2119457857-21	Acute toxicity Category 4; H302 Specific target organ toxicity - repeated exposure Category 2; H372	$\geq 2.5 - < 5$
Sodium Xylenesulfonate	1300-72-7 215-090-9 01-2119513350-56	Eye irritation Category 2; H319	$\geq 1 - < 2.5$
Fatty alcohol ethoxylates > 5EO		Acute toxicity Category 4; H302 Serious eye damage Category 1; H318	$\geq 1 - < 2.5$

Product AT USE DILUTION

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	ClassificationREGULATION (EC) No 1272/2008	Concentration: [%]
Phosphoric acid	7664-38-2 231-633-2 01-2119485924-24	Skin corrosionCategory 1B; H314 Corrosive to metalsCategory 1; H290	$\geq 2.5 - < 5$
Alkylamineoxides	61791-46-6 263-179-6	Acute toxicityCategory 4; H302 Acute aquatic toxicityCategory 1; H400 Serious eye damage/eye irritationCategory 2; H319 Skin corrosion/irritationCategory 2; H315	$\geq 0.25 - < 0.5$
Substances with a workplace exposure limit :			
Diethylene Glycol	111-46-6 203-872-2 01-2119457857-21	Acute toxicityCategory 4; H302 Specific target organ toxicity - repeated exposureCategory 2; H372	$\geq 0.1 - < 0.25$

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

Product AS SOLD

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Oasis Pro Toilet

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Product AT USE DILUTION

In case of eye contact : Rinse with plenty of water.

In case of skin contact : Rinse with plenty of water.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Decomposition products may include the following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Oasis Pro Toilet

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.

For personal protection see section 8.

See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Use only with

Oasis Pro Toilet

adequate ventilation. Wash hands thoroughly after handling. Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities**Product AS SOLD**

Requirements for storage areas and containers : Keep away from strong bases. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Keep only in original container. Absorb spillage to prevent material damage.

Storage temperature : 0 °C to 40 °C

Packaging material : Suitable material: Plastic material
Unsuitable material: Aluminium, Mild steel

Product AT USE DILUTION

Requirements for storage areas and containers : Keep away from strong bases. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses**Product AS SOLD**

Specific use(s) : Sanitary cleaner. Manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
--

8.1 Control parameters**Product AS SOLD****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Phosphoric acid	7664-38-2	TWA	1 mg/m ³	UKCOSSTD
		STEL	2 mg/m ³	UKCOSSTD
Diethylene Glycol	111-46-6	TWA	23 ppm 101 mg/m ³	UKCOSSTD
Further information	2	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used		

DNEL

phosphoric acid	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Acute local effects
-----------------	---	--

Oasis Pro Toilet

	Value: 2 mg/m3
	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1 mg/m3
	End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 0.73 mg/m3

8.2 Exposure controls**Product AS SOLD****Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advice).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, 89/686/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Product AT USE DILUTION**Appropriate engineering controls**

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Oasis Pro Toilet**Individual protection measures**

Hygiene measures	: Wash hands before breaks and immediately after handling the product.
Eye/face protection (EN 166)	: No special protective equipment required.
Hand protection (EN 374)	: No special protective equipment required.
Skin and body protection (EN 14605)	: No special protective equipment required.
Respiratory protection (EN 143, 14387)	: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, 89/686/EEC), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice	: Consider the provision of containment around storage vessels.
----------------	---

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

	Product AS SOLD	Product AT USE DILUTION
Appearance	: liquid	liquid
Colour	: clear, dark blue	blue
Odour	: pleasant	odourized
pH	: 0.1 - 0.5, 100 %	1.2 - 1.4
Flash point	: Not applicable., Does not sustain combustion.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Relative density	: 1.4 - 1.5	
Water solubility	: soluble	

Oasis Pro Toilet

Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

Product AS SOLD

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Aluminium
Mild steel

10.6 Hazardous decomposition products

Decomposition products may include the following materials:

Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides
Oxides of phosphorus

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Oasis Pro Toilet

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: There is no data available for this product.
Acute dermal toxicity	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.
Aspiration toxicity	: There is no data available for this product.

Components

Acute oral toxicity	: Phosphoric acid LD50 rat: 2,600 mg/kg Alkylamineoxides LD50 rat: 1,041 mg/kg Diethylene Glycol LD50 Humans: 1,120 mg/kg Sodium Xylenesulfonate LD50 rat: 7,000 mg/kg
---------------------	---

Components

Acute inhalation toxicity	: Phosphoric acid 4 h LC50 rat: 0.962 mg/l
---------------------------	---

Components

Acute dermal toxicity	: Phosphoric acid LD50 rabbit: 2,000 mg/kg Diethylene Glycol LD50 rabbit: 13,300 mg/kg
-----------------------	---

Potential Health Effects

Product AS SOLD

Eyes	: Causes serious eye damage.
Skin	: Causes severe skin burns.
Ingestion	: Causes digestive tract burns.

Oasis Pro Toilet

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Product AS SOLD

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

Product AS SOLD

12.1 Ecotoxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Alkylamineoxides
96 h LC50 Fish: 1 mg/l

Diethylene Glycol
96 h LC50 Pimephales promelas (fathead minnow): 75,200 mg/l

Components

Oasis Pro Toilet

Toxicity to daphnia and other aquatic invertebrates : Phosphoric acid
48 h EC50 Daphnia magna (Water flea): > 100 mg/l

Diethylene Glycol
24 h EC50 Daphnia magna (Water flea): > 10,000 mg/l

Components

Toxicity to algae : Phosphoric acid
72 h EC50 Desmodesmus subspicatus (green algae): > 100 mg/l

Diethylene Glycol
96 h EC50: 9,362 mg/l

Sodium Xylenesulfonate
96 h EC50: 230 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : Phosphoric acid
Result: Not applicable - inorganic

Alkylamineoxides
Result: Readily biodegradable.

Diethylene Glycol
Result: Readily biodegradable.

Sodium Xylenesulfonate
Result: Biodegradable

Fatty alcohol ethoxylates > 5EO
Result: Biodegradable

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Oasis Pro Toilet**12.6 Other adverse effects**

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods**Product AS SOLD**

- | | |
|-----------------------------------|---|
| Product | : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : Inorganic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Product AT USE DILUTION

- | | |
|------------------------|--|
| Product | : Diluted product can be flushed to sanitary sewer. |
| Contaminated packaging | : Dispose of in accordance with local, state, and federal regulations. |

Section: 14. TRANSPORT INFORMATION**Product AS SOLD**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- | | |
|-----------------------------------|----------------------------|
| 14.1 UN number | : 1805 |
| 14.2 UN proper shipping name | : PHOSPHORIC ACID SOLUTION |
| 14.3 Transport hazard class(es) | : 8 |
| 14.4 Packing group | : III |
| 14.5 Environmental hazards | : No |
| 14.6 Special precautions for user | : None |

Air transport (IATA)

- | | |
|-------------------------|-----------------------------|
| 14.1 UN number | : 1805 |
| 14.2 UN proper shipping | : Phosphoric acid, solution |

Oasis Pro Toilet

name
 14.3 Transport hazard : 8
 class(es)
 14.4 Packing group : III
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number : 1805
 14.2 UN proper shipping name : PHOSPHORIC ACID SOLUTION
 14.3 Transport hazard : 8
 class(es)
 14.4 Packing group : III
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None
 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : 5 % or over but less than 15 %: Non-ionic surfactants
 less than 5 %: Anionic surfactants, Polycarboxylates
 Other constituents: Perfumes
 Allergens:
 Hexyl cinnamal
 d-Limonene
 2-(4-tert-Butylbenzyl) propionald-hyd
 Coumarin

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
 The Control of Substances Hazardous to Health Regulations.
 Health and Safety at Work Act.

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Corrosive to metals 1, H290	Calculation method
Skin corrosion 1A, H314	On basis of test data.

Oasis Pro Toilet

Serious eye damage 1, H318

On basis of test data.

Full text of H-Statements

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response; GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

Oasis Pro Toilet

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ANNEX: EXPOSURE SCENARIOS**DPD+ Substances:**

The following substances are the lead substances that contribute to the mixture Exposure Scenario according to the DPD+ Rule:

Route	Substance	CAS-No.	EINECS-No.
Ingestion	Phosphoric acid	7664-38-2	231-633-2
Inhalation	Phosphoric acid	7664-38-2	231-633-2
Dermal	Phosphoric acid	7664-38-2	231-633-2
Eyes	Phosphoric acid	7664-38-2	231-633-2
aquatic environment	Alkylamineoxides	61791-46-6	263-179-6

Physical properties DPD+ Substances:

Substance	Vapour pressure	Water solubility	Pow	Molar Mass
Phosphoric acid	4 Pa	> 850 g/l		98 g/mol

To calculate if your downstream Operating Conditions and Risk management Measures are safe, please calculate your risk factor at the website below:

www.ecetoc.org/tra

Short title of Exposure Scenario : **Sanitary cleaner. Manual process**

Use descriptors

Main User Groups : Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Sectors of end-use : **SU22:** Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories : **PROC10:** Roller application or brushing
PROC8a: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Product categories : **PC35:** Washing and cleaning products (including solvent based products)

Oasis Pro Toilet

Environmental Release Categories : **ERC8a:** Wide dispersive indoor use of processing aids in open systems